

COMPACTOR TYRES

- Speedways compactor tyres are engineered to provide equal distribution of ground pressure across the tyre & to give optimum compaction.
- Tread compound specially formulated to endure high temperatures and minimize loose materials sticking to tyres.



	SIZE	PATTERN	PLY RATING	RIM WIDTH		TUBETYPE/TUBELESS	SECTION WIDTH		OVERALL DIAMETER		LOAD CAPACITY				INFLATION PRESSURE	
				STANDARD	ALTERNATIVE		(mm)	(inch)	(mm)	(inch)	8KPH / 5MPH MAX LOAD		16KPH / 10MPH MAX LOAD			
				(inch)	(inch)						(kg)	(lbs)	(kg)	(lbs)		
15"	7.50-15	ROADKING	6	6.0	6.5	TUBETYPE	225	8.9	790	31.1	1770	3894	1415	3113	3.8	54
		ROADKING	14	6.0	6.5	TUBETYPE	225	8.9	790	31.1	2750	6050	2225	4895	7.8	110
	8.5/90-15	ROADKING	6	6.0	6.5	TUBELESS	230	9.0	786	31.0	1770	3894	1415	3113	3.4	48
20"	9.00-20	ROADKING	12	7.0	7.5	TUBETYPE	275	10.8	1020	40.1	4060	8932	3245	7139	6.2	88
		ROADKING	14	7.0	7.5	TUBETYPE	275	10.8	1020	40.1	4420	9724	3540	7788	7.2	102
	11.00-20	ROADKING	16	8.0	8.5	TUBETYPE	305	12.0	1085	42.7	5440	11968	4350	9570	7.2	102
		ROADKING	18	8.0	8.5	TUBETYPE	305	12.0	1085	42.7	5910	13002	4730	10406	8.3	118