

# EARTHMOVER TYRES

- The special non-directional tread design formulated with silica based tread compound, together with a heavy duty nylon carcass makes it capable of withstanding cuts, snags and bruises under all service conditions.



	SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE	
				(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)
20"	9.00-20	ROCK LUG	18	7.5	TUBETYPE	260	10.2	1035	40.7	476	18.7	3056	120.3	18	23	2325	5115	7.2	102
	10.00-20	ROCK LUG	20	8.0	TUBETYPE	275	10.8	1075	52.3	494	19.4	3171	124.8	20	25	2690	5918	7.2	102
24"	14.00-24	ROCK LUG	24	10.0	TUBELESS	375	14.7	1368	53.8	635	25.0	4039	159.0	25	31	5150	11350	5.7	81
25"	14.00-25	ROCK LUG	24	10.0	TUBELESS	375	14.8	1375	54.1	635	25.0	4039	159.0	25	31	5150	11350	5.7	81
	15.5-25	ROCK LUG	12	12.0	TUBELESS	394	15.5	1278	50.3	569	22.4	3658	144.0	25	31	3250	7150	2.5	36
		ROCK LUG	16	12.0	TUBELESS	394	15.5	1278	50.3	569	22.4	3658	144.0	25	31	3650	8050	3.0	42
	17.5-25	ROCK LUG	16	14.0	TUBELESS	435	17.0	1345	52.9	635	25.0	3955	157.0	28	35	4250	9350	3.0	43
	20.5-25	ROCK LUG	16	17.0	TUBELESS	531	20.9	1483	58.4	686	27.0	4394	173.0	31	39	5461	12015	3.0	43
	23.5-25	ROCK LUG			TUBELESS														

UNDER DEVELOPEMENT