

# GRADER (G2) TYRES

- Rugged sturdy tyres for drive wheels of off-the-road equipment.
- Tough carcass and special trade compound with weather & ozone resistant properties to withstand cuts, snags & bruises in the most severe operating conditions.
- An open spaced traction pattern with self cleaning property provides traction capability, ideally suited for graders.



	SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE	
				(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)
24"	13.00-24	POWERGRIP	12	8.0	TUBELESS	341	13.4	1280	50.4	584	23.0	3785	149.0	25	31	2725	6000	3.0	43
		POWERGRIP	16	8.0	TUBELESS	341	13.4	1280	50.4	584	23.0	3785	149.0	25	31	3000	6600	3.5	50
	14.00-24	POWERGRIP	12	10.0	TUBELESS	375	14.7	1350	53.1	610	23.0	4013	158.0	25	31	3075	6750	2.8	40
		POWERGRIP	16	10.0	TUBELESS	375	14.7	1350	53.1	610	24.0	4013	158.0	25	31	3650	8050	3.8	54