

# SKID STEER TYRES

**STEERKING +** - Widewall tyre with side wall and rim guard protectors, meant for the value conscious performance oriented applications.

**STEERKING +**



	SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE	
				(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)
16.5"	10-16.5	STEERKING +	10	8.25	TUBELESS	268	10.5	795	31.3	356	14.0	2286	90.0	15	19	2140	4700	5.2	74
	12-16.5	STEERKING +	12	9.75	TUBELESS	312	12.3	825	32.5	381	15.0	2438	96.0	16	20	2765	6083	5.2	74

**STEER PLUS HD**- Premium tyre with extra deep tread & thick sidewalls providing better traction, puncture resistance and longer life. Specially designed rim guard ensures greater protection against flats & wheel damage in the rim flange area.

**STEER PLUS HD**



	SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE	
				(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)
12"	23X8.50-12	STEER PLUS HD	6	7.0	TUBELESS	216	8.5	584	23.0	254	10.0	1727	68.0	12	15	822	1808	3.5	50
15"	27X8.50-15	STEER PLUS HD	8	7.0	TUBELESS	218	8.6	676	26.6	305	12.0	2006	79.0	12	15	1314	2890	4.2	60
16.5"	31X13-16.5	STEER PLUS HD	14	9.75	TUBELESS	330	12.9	805	31.6	356	14.0	2337	92.0	19	24	2435	5350	4.8	68
	33X15.5-16.5	STEER PLUS HD	14	12.0	TUBELESS	394	15.5	838	33.0	381	15.0	2464	97.0	19	24	3152	6935	5.2	74
17.5"	14-17.5	STEER PLUS HD	14	10.5	TUBELESS	350	13.7	940	37.0	406	16.0	2743	108.0	26	33	3900	8580	5.4	77
19.5"	15-19.5	STEER PLUS HD	14	11.8	TUBELESS	401	15.8	1036	40.7	457	18.0	3048	120.0	26	33	4570	10054	5.6	79

**ROCKPLUS HD** - Deep tread, extra thick sidewall & tough casing ensures longer life. Silica & natural rubber base compound provides greater chip & tear resistance.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		
			(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)	
16.5"	10-16.5	ROCK PLUS HD	12	8.25	TUBELESS	268	10.5	790	31.1	356	14.0	2286	90.0	30	38	2140	4700	5.2	74
	12-16.5	ROCK PLUS HD	14	9.75	TUBELESS	325	12.8	866	34.1	381	15.0	2438	96.0	30	38	2765	6083	5.2	74

**ROCK MASTER**- Deeper depth tyre tread for longer life. Bigger and sturdier blocks. Excellent chip & tear resistance compound. Extra thick sidewall with rim guard gives protection against damages



SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		
			(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)	
16.5"	10-16.5	ROCK MASTER	12	8.25	TUBELESS	267	10.5	790	31.1	356	14.0	2337	92	30	37	2180	4796	5.3	75
	12-16.5	ROCK MASTER	14	9.75	TUBELESS	325	12.8	856	33.7	381	15.0	2514	99	34	43	2765	6083	4.9	70

**STEERKING HD + -** Premium conventional skid steer tyre with deeper tread depth, premium compound, larger tread lugs & Heavier sidewall.



	SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE	
				(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)
16.5"	10-16.5	STEERKING HD+	8	8.25	TUBELESS	268	10.5	795	31.3	356	14.0	2286	90.0	16	20	1875	4125	4.2	60
		STEERKING HD+	10	8.25	TUBELESS	268	10.5	795	31.3	356	14.0	2286	90.0	16	20	2140	4700	5.2	74
	12-16.5	STEERKING HD+	10	9.75	TUBELESS	325	12.8	855	33.6	381	15.0	2438	96.0	20	25	2545	5560	4.5	64
		STEERKING HD+	12	9.75	TUBELESS	325	12.8	855	33.6	381	15.0	2438	96.0	20	25	2765	6083	5.2	74

**MONSTER -** Extra deep tread with sturdy lug design. Strong casing with heat and cut resistant tread compound provides longer life. Extra thick sidewall with rim guard gives protection against damages.



	SIZE	PATTERN	PLY RATING	RIM WIDTH	TUBETYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE	
				(inch)		(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	(kg)	(lbs)	(bar)	(psi)
16.5"	10-16.5	MONSTER	12	8.25	TUBELESS	259	10.2	798	31.4	366	14.4	2337	92.0	34.0	43.0	2180	4806	4.5	60
	12-16.5	MONSTER	14	9.75	TUBELESS	307	12.1	838	33.0	384	15.1	2515	99.0	35.0	44.0	2765	6083	4.9	70
17.5"	14-17.5	MONSTER	14	10.5	TUBELESS	358	14.1	935	36.8	427	16.8	2743	108.0	35.0	44.0	3900	8580	5.5	80